



Product	Cable	Rating						
Centerage dewatering submersible electric pump is ideal for dewatering buildings yard, drainage water in flooded areas, dam construction sites, harbor work, power stations, mines, etc.	Direct on line 2 (4*10)	3~ Rated output 22 kw Speed of rotation 2950 rpm						
Denomination	Monitoring equipment							
Product code DD 100/4/22 Discharge connection 4 "	Thermal contacts	<table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th>Voltage V</th> <th>Rated current A</th> <th>Starting current A</th> </tr> </thead> <tbody> <tr> <td>380/660</td> <td>44</td> <td>88</td> </tr> </tbody> </table>	Voltage V	Rated current A	Starting current A	380/660	44	88
Voltage V	Rated current A		Starting current A					
380/660	44		88					
Process data	Material							
Liquid temperature Max +40°C Depth of immersion Max 20m The PH of the liquid PH5-8 Liquid density Max 1100kg/m	Outer casing Steel Impeller Wear resistance steel Wear parts Rubber-liner Stator housing Cast iron GG25 Strainer Steel Shaft Stainless steel 420 O-ring Viton Rubber							
Motor data	Mechanical face seals							
Squirrel cage 3-phase induction motor Frequency 50HZ Insulation class H (+180°C) Ingress of protection IP68 Voltage variation -continuously running Max ±5% -intermittent running Max ±10% Voltage imbalance between phases max 2% No. of start/hour max 15	Upper silicon carbide/carbon Lower tungsten carbide /silicon carbide							
	Options							
	Rubber-lined wear parts Discharge connector with coupling 6'' Various cable size.							
	Accessories							
	Hose connection and other mechanical accessories. Electrical accessories such as controller, control panels, starter, monitoring relays, cables.							